



## DORSODURO 750 ABS

### Technical chart

Engine	Aprilia four stroke 90° longitudinal V twin. Double overhead camshaft with mixed gear/chain drive; four valves per cylinder. 3 maps Ride-by-Wire System.
Displacement	749.9 cc
Maximum power	92 HP (67,3 kW) @ 8.750 rpm
Maximum torque	8,4 kgm (82 Nm) @ 4.500 rpm
Cooling	Liquid cooling
Front suspension	Ø43 mm Sachs upside-down. Spring preload and hydraulic rebound adjustable. 160 mm wheel travel.
Rear suspension	Aluminium alloy swingarm. Hydraulic Sachs monoshock absorber. Spring preload and hydraulic rebound adjustable. Wheel travel: 155 mm.
Front brake	Double stainless steel floating wave disc (Ø 320 mm). Four-piston radial calipers. Metal braided brake line. 2 channels Continental ABS.
Rear brake	Stainless steel wave disc (Ø 240 mm) with single piston caliper. Metal braided brake line. 2 channels Continental ABS.
Front tyre	Radial tubeless - 120/70 ZR 17
Rear tyre	Radial tubeless - 180/55 ZR 17
Seat height	870 mm
Fuel tank	12 lt
Emissions	Euro 3 homologation